



ROTARY MOWERS WITH WINGS

DR / MV
Series



VARIABLE WIDTH

The series DR variable width mowers consist of a rigid central section with an adjustable wing mounted on either side. The wings are operated by hydraulic rams which move smoothly and independently open and closed, to allow for an easy and exact adjustment of the cutting width in orchards and vineyards with different row widths.

For professional maintenance in orchards. Large capacity or one machine for multiple orchard setups. Strong cost reduction / ha.



DR/MV SERIES

Rotary mowers with wings



The optional cantilever design headstock enables the mower to be pulled rather than pushed. This protects the machine and provides a full floatation effect. A double headstock for front and rear mount is optionally available too.

There is a small amount of float on the wings to allow for undulating ground. For ground that is seriously undulating or not level with the central alley, raisable wings (shown above) are available as an option.

EXCELENT CUT AND GRAS DISTRIBUTION

Two gearboxes rotating in opposite directions assure an excellent throw out and distribution of the cut material either behind the machine or to the left and right hand side on the tree strips.



EXTRA'S

- Manual or hydraulic parallelogram-type offset device
- "Perfect" pulling type headstock for front mount
- Double headstock for front and rear mount
- Mow-spray combination feature
- Tandem roller
- Full rubber wheels
- Raisable wings

TECHNICAL SPECIFICATIONS	DR-250	MV-280	DR-280	MV-320	DR-320	DR-365	DR-405	DR-440	DR-480	DR-570
Min. cutting width (cm/inch)	150 / 4'11"	190 / 6'3"	175 / 5'9"	195 / 6'5"	190 / 6'3"	225 / 7'5"	245 / 8'2"	290 / 9'6"	290 / 9'6"	290 / 9'6"
Max. cutting width (cm/inch)	250 / 8'3"	280 / 9'2"	280 / 9'2"	320 / 10'6"	320 / 10'6"	365 / 12'0"	405 / 13'4"	440 / 14'6"	480 / 15'9"	570 / 15'8"
Min. power required at 50 rpm of pto (kW/HP)	28 / 38	29 / 40	29 / 40	36 / 50	36 / 50	40 / 55	40 / 55	48 / 65	50 / 68	60 / 82
Number of blades	4	4	5	4	5	5	5	5	5	7
Total width (cm/inch)	161 / 5'3"	193 / 6'4"	178 / 5'10"	205 / 6'9"	193 / 6'4"	228 / 7'6"	248 / 8'3"	300 / 9'10"	300 / 9'10"	300 / 9'10"
Cutting height (cm/inch)	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½	4-9 / 1½-3½
Weight (kg/lbs)	540 / 1188	580 / 1275	600 / 1323	625 / 1157	615 / 1375	660 / 1455	710 / 1565	740 / 1628	825 / 1815	1100 / 2420

As our policy is one of continuous improvement, we reserve the right to change the specification or to modify the desing without prior notice



Van Wamel B.V.

📍 **Van Wamel B.V.**
Energieweg 1, 6658 AE
Beneden Leeuwen
The Netherlands

☎ +31 (0) 487 59 29 44
☎ +31 (0) 487 59 29 44
@ www.perfectvanwamel.com
📧 perfect@vanwamel.nl

Your PERFECT dealer